



## UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.		FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/541,352	10/541,352 07/05/2005		Gerhard Jonke	2002P00148WOUS	8235
28204	7590	01/24/2006		EXAMINER	
SIEMENS		EIZ AL PROPERTY	CABRERA, ZOILA E		
ALBISRIE			ART UNIT	PAPER NUMBER	
ZURICH,	CH-804	7	2125		
SWITZERL	AND		DATE MAILED: 01/24/2006		

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)				
	10/541,352	JONKE ET AL.				
Office Action Summary	Examiner	Art Unit				
	Zoila E. Cabrera	2125				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING D.  Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication.  If NO period for reply is specified above, the maximum statutory period of Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be timwill apply and will expire SIX (6) MONTHS from a cause the application to become ABANDONE	L. lely filed the mailing date of this communication. D (35 U.S.C. § 133).				
Status						
1)⊠ Responsive to communication(s) filed on <u>05 Jalestians</u> 2a)□ This action is <b>FINAL</b> . 2b)⊠ This 3)□ Since this application is in condition for allowance closed in accordance with the practice under <u>Balactical States</u> .	s action is non-final. nce except for formal matters, pro					
Disposition of Claims						
4) ⊠ Claim(s) 1-18 is/are pending in the application 4a) Of the above claim(s) is/are withdra 5) □ Claim(s) is/are allowed. 6) ⊠ Claim(s) 1-18 is/are rejected. 7) □ Claim(s) is/are objected to. 8) □ Claim(s) are subject to restriction and/or	wn from consideration.					
Application Papers						
9) The specification is objected to by the Examine 10) The drawing(s) filed on is/are: a) accomposed applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) The oath or declaration is objected to by the Examine 11.	epted or b) objected to by the bedrawing(s) be held in abeyance. See tion is required if the drawing(s) is obj	e 37 CFR 1.85(a). lected to. See 37 CFR 1.121(d).				
Priority under 35 U.S.C. § 119						
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>						
Attachment(s)  1) Notice of References Cited (PTO-892)	4) 🔲 Interview Summary	(PTO.413)				
<ol> <li>Notice of References Cited (PTO-692)</li> <li>Notice of Draftsperson's Patent Drawing Review (PTO-948)</li> <li>Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)</li> <li>Paper No(s)/Mail Date 7/5/05: 1/9/06.</li> </ol>	Paper No(s)/Mail Da					

## **DETAILED ACTION**

## Claim Rejections - 35 USC § 102

**1.** The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claims 1-3, 6, 7-8, 14-18 are rejected under 35 U.S.C. 102(e) as being anticipated by **Yoriki et al. (US 6,640,431 B1)**.

Regarding claim 1, **Yoriki** discloses a multiple insertion head for mounting components onto substrates, comprising a carrier arranged such that it can rotate about a rotational axis (Fig. 2; Col. 1, lines 18-23), and a plurality of receiving tools arranged such that they can be moved in a mounting direction at an angle to the rotational axis (fig. 2, element 90); the receiving tools being arranged on the carrier and arranged so as to receive the components (Col. 1, line 59 to Col. 2, line 7), such that each receiving tool is provided with at least one of an active drive and sensors

As for claims 2-3, 6, 7-8, 14-18, Yoriki further discloses,

(Fig. 14, drives and sensors).

Art Unit: 2125

2. Multiple insertion head according to claim 1, with each receiving tool having its own rotary drive by means of which received components can in each case be rotated about a tool axis arranged at an angle to the rotational axis (D) of the multiple insertion head (Fig. 14, nozzle rotating servo motor).

- 3. The multiple insertion head according to claim 1, wherein each receiving tool comprises a vacuum generator (Col. 1, lines 60-61, suction nozzle).
- 6. The multiple insertion head according to claim 1, further comprising a blast air vacuum device arranged in a receiving mounting position of one of the receiving tools, the vacuum device further arranged such that therein components can be received or mounted by means of the receiving tool located in the receiving mounting position, the receiving tool being connected such that an additional vacuum can be applied or generated to the receiving tools for receiving the components <u>or</u> in addition a blast air impulse while mounting the components in the receiving tool located in the receiving mounting position (Col. 1, lines 60-51, i.e. one suction nozzle holding, by suction, an EC; Col. 16, lines 5-9).
- 7. The multiple insertion head according to claim 1, wherein each receiving tool comprises a tool shaft embodied as a hollow shaft running coaxially to the tool axis and a rotary sensor arranged so as to detect an angle position of the tool shaft (Col. 16, lins 19-34 and lines 53-61).

Art Unit: 2125

8. The multiple insertion head according to claim 7, wherein each tool shaft comprises a vacuum pipettes at a distal end range (Col. 16, lines 6-15).

- 14. The multiple insertion head according to claim 1, wherein the carrier comprises at least one control device arranged so as to control and/or regulate the active drives and/or sensors (Fig. 14).
- 15. The multiple insertion head according to claim 14, wherein the control unit comprises at least one digital signal processor by means of which one or a plurality of the active drives or sensors can be controlled (Fig. 14).
- 16. The multiple insertion head according to claim 1, further comprising, a linear motor arranged such that a receiving tool found in the receiving mounting position can be moved in the mounting direction provided that the linear motor is engaged in the receiving tool (Fig. 14).
- 17. The multiple insertion head according to claim 16, further comprising an engaging element provided in each receiving tool so as to engage in an engaging piece of the runner of the linear motor (Col. 18, lines 42-46 and lines 64-66).
- 18. The multiple insertion head according to claim 16, further comprising an additional retracting means interacting with the linear motor by means of which a runner of the

Art Unit: 2125

linear motor is pretensioned by means of a spring tension against the force of gravity and in which the pretensioning is compensated for by compressed air when the insertion head is in operation (Col. 18, lines 42-62).

## Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 4-5 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yoriki et al. (US 6,640,431 B1) in view of Gieskes et al. (US 2004/0074085 A1).

Yoriki discloses the limitations of claims 1 and 3 above but fails to disclose the limitations of claims 4-5. However, **Gieskes** discloses such limitations as follows:

- 4. The multiple insertion head according to claim 3, wherein the vacuum generators comprises a Venturi tubes and the carrier comprises a hollow shaft running coaxially to the rotational axis to which the receiving tools are fitted such that compressed air can be conveyed through the hollow shaft of the carrier to the Venturi tubes ([0026]).
- 5. The multiple insertion head according to claim 3, wherein the Venturi tubes is connected to a regulator to control pressure ([0028]-[0029]).

Art Unit: 2125

Therefore, it would have been obvious to a person of the ordinary skill in the art at the time the invention was made to combine the teachings of **Yoriki** with the integrated air flow control for a pick and place spindle assembly as taught by **Gieskes** because it would provide an improved system by minimizing the time required for the vacuum for air pressure to be applied to the nozzle tip ([0011]).

3. Claims 9-13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yoriki et al. (US 6,640,431 B1) in view of Asai et al. (US 5,588,195).

Yoriki discloses the limitations of claim 1 above but fails to disclose the limitations of claims 9-13. However, Asai discloses such limitations as follows:

- 9. The multiple insertion head according to claim 1, further comprising a rotationally symmetrical energy and data transmission device arranged between the carrier and a housing of the multiple insertion head, the transmission device arranged such that at least one of active drives and sensors can be supplied with energy and by which the data from the sensors and the data to the sensors can be transmitted with a first transmitter part being permanently fitted to the housing of the multiple insertion head and a second transmitter part being permanently fitted to the carrier in such a way that it can rotate (Abstract; Fig. 13; Col. 2, lines 55-67).
- 10. The multiple insertion head according to claim 9, wee wherein the transmission device hang-comprises at least one slip ring (Col. 2, lines 2-9).

Art Unit: 2125

11. The multiple insertion head according to claim 9, wherein the data transmission device comprises one pair of electromagnetic transmitters and one pair of capacitive transmitters arranged rotationally symmetrical around the rotational axis of the multiple insertion head and by means of which there is non-contact transmission of both the energy and the data (Col. 3, line 40 to Col. 4, lines 6).

- 12. The multiple insertion head according to claim 11, wherein the capacitive transmitter, comprises a plate-shaped antenna in the first transmitter part and in the second transmitter part the first transmitter part the electromagnetic transmitter comprises a circular magnetically conductive body with a u-shaped cross section open in the direction of the carrier and a circular magnetically conductive body in the second transmitter part comprising a rectangular cross section which is arranged in such a way in the opening of the first transmitter part that the direction of the magnetic field used for the transmission of energy is at right angles to the direction of the electrical field used for the transmission of data (Fig. 8, element 316).
- 13. The multiple insertion head according to claim 9, comprising at least one polished disk arranged on the housing and on the carrier such that the polished disks are arranged immediately next to each other so that compressed air and a vacuum can be applied from external vacuum generators to the active drives of the carrier (Col. 9, lins 30-44).

Therefore, it would have been obvious to a person of the ordinary skill in the art at the time the invention was made to combine the teachings of **Yoriki** with the

Art Unit: 2125

electronic component mounting apparatus of **Asai** because it would provide an improved mounting apparatus with a high durability (Col. 1, lines 6-10; Col. 2, lines 25-

31).

Conclusion

4. The prior art made of record and not relied upon is considered pertinent to

applicant's disclosure.

Any inquiry concerning communication or earlier communication from the

examiner should be directed to Zoila Cabrera, whose telephone number is (571) 272-

3738. The examiner can normally be reached on M-F from 8:00 a.m. to 5:30 p.m. EST

(every other Friday).

If attempts to reach the examiner by phone fail, the examiner's supervisor, Leo

Picard, can be reached on (571) 272-3749. Additionally, the fax phones for Art Unit

2125 are (571) 273-8300. Any inquiry of a general nature or relating to the status of this

application should be directed to the group receptionist at (703) 305-9600.

Zoila Cabrera

Patent Examiner

1/19/06